

DRY FILM MOLY LUBRICANT



LU™ 200



TM

For use in extreme pressure applications



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 131583)



Minimum - Maximum operational temperature range: Low -30 °F (-34 °C) • High 650 °F (343 °C)



HMS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)



Features EZ-Touch® comfort nozzle

- Withstands extreme pressures up to 50,000 psi
- Works from -30F - 650F (750F intermittently)
- Non-conductive
- Low coefficient of friction



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 200 Dry Film Moly Lubricant is a high solids, molybdenum disulfide coating that withstands extreme pressures and high temperatures. This product bonds to all clean surfaces that are not adversely affected by alcohol or aromatic hydrocarbons, resulting in a high performance dry film lubricant that will perform when you need it.

LUBRICANTS

USES

- Assembly and run-in lubrication
- Automotive and industrial gaskets
- Machine tool sliding surfaces and gears
- Tumbler locks
- Intricate mechanisms
- Mating surfaces of machine parts
- Parking meters
- Vending machines
- Bearings
- Chutes and bins
- Chain drives



LU200

© 2010 Sprayon® Products Made in U.S.A.

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70°F.). Shake well before using. Spray at a distance of 8" to 10" from surface.

PERFORMANCE

PLASTIC SAFE: No

TEMPERATURE RANGE:

LOW: -30°F

HIGH: 650°F constant (750°F) intermittent

LOAD CAPACITY: Extreme Pressure

DRYING: Dry time to touch is 5 minutes.

Dry time to handle is 10 minutes.

Cures in 2 hours at room temperature.

COEFFICIENT OF FRICTION

(ASTM D-4518): .23

•NSF Registration Number 131583; H2 Rated

•Penetrant

•Water-Displacer

•Rust Inhibitor

•Works as boundary lube to as cold as -200°F

PROPERTIES

APPEARANCE: Dull black solid film

ODOR: Mild solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.69

SPECIFIC GRAVITY: 0.71

PAINTABLE: No

H.A.P.S. (Hazardous Air Pollutants): No

SARA 313 Chemicals: No

% VOC AEROSOL: 67.30%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00200

UPC Code:

0-75577-90200-2

Fill Wt.: 11 oz.

Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:

866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

1-800-777-2966

310-PDS-LU200